

Lead institution:	University of São Paulo	
Supervisor name: José R. Simões Moreira	Supervisor department: Mechanical Engineering	
Co-supervisor: Bruno Souza Carmo	Co-supervisor department: Mechanical Engineering	
Recipient: TO BE APPOINTED	Type: Post Doc	
Project title: Numerical modelling and optimisation of a reactor for solar thermal methane reforming		
Research theme area: Numerical modelling, numerical simulation, design, optimisation, solar thermal steam methane reforming, hydrogen production		
<p>Aims Numerical modelling and simulation of a receiver-reactor of solar thermal steam methane reformer in order to provide a tool for design and optimisation. We will work at lab and pilot scale, using parabolic dish as solar concentrator. The design should maximise the hydrogen yield.</p>		
<p>Abstract Hydrogen can be used either in fuel cells, which generates electricity and water vapour, or in an internal combustion engine, which generates mechanical power and water vapour. Transport powered by hydrogen does not produce any direct CO₂ emissions. The environmental impact of using hydrogen as transportation fuel depends on the source of the energy used to produce the hydrogen. In this sense, the ideal scenario is to have hydrogen produced entirely from renewable sources. However, the technologies available for that have shown very small efficiency. Consequently, most of the hydrogen produced today is sourced from fossil fuels, with the principal method employed being the catalytic reforming of methane, CH₄, the principal component of natural gas and other gaseous fuels.</p> <p>The reforming reaction is highly endothermic, and is, thus, favoured by high temperatures; industrial reforming processes are carried out between 800 °C and 1000 °C. The required energy is usually supplied by combustion of additional natural gas and process waste gas from the downstream hydrogen purification step. The share of natural gas consumed as fuel varies from 3% to 20% of the total plant's natural gas consumption. The reaction gas product mixture is known as synthesis gas (syngas): a gas mixture that contains varying amounts of CO and H₂ whose exothermic conversion into fuel and other products has long been commercially employed, for example, via the Fischer-Tropsch technology.</p> <p>Methane reforming technologies are not carbon neutral unless bio-methane or other bio-derived resources are used, but this is not competitive in terms of cost nowadays. However, although methane from natural gas reform is not carbon neutral, there is the advantage of concentrating the CO₂ production in a large industrial facility, where efficiency optimisation can be more easily carried out, carbon capture and storage techniques may be possibly employed and wide spread of green house gases and pollutants in highly populated areas (i.e., cities) can be avoided. In addition, reforming carbon based fuels into hydrogen using renewable energy, such as solar concentrated power, can reduce CO₂ emissions of at least 25% when compared to using them directly as fuels and also bring economical savings. In doing so, solar energy is embodied thermochemically in the product hydrogen, being thus able to be stored at ambient conditions, transported from the point of production to where it is required, and used outside daylight hours. Such a transitional</p>		

technology is considered by many to be an essential stepping stone from current practice to a truly renewable-based hydrogen economy.

In this project, we intend to employ numerical modelling and simulation to design and optimise a receiver-reactor of solar thermal steam methane reformer in order to provide a tool for design and optimisation in terms of maximisation of hydrogen yield. We will work at lab and pilot scale, using parabolic dish as solar concentrator. The focus will be on direct, volumetric absorbers with a structured stationary matrix with the catalysts necessary for the reactions. The model should be able to represent the heat transfer, flow dynamics and chemical reactions that occur inside the reactor. The model and designs can be validated using the experimental facility developed in a companion PhD project developed within project 16 of the RCGI.